

# SID Galaxy APOLLO UV

## Datasheet



Parameters	APOLLO 25T40	APOLLO 25T42	APOLLO 25T60	APOLLO 25T62	APOLLO 25T80
<b>Printhead Type</b>	Toshiba CE4M 636 nozzles • Variable Dot • 5 • 10 • 15 picoliters				
<b>Number of Printheads</b>	4	6	6	8	8
<b>Resolution</b>	Up to 4800 dpi				
<b>Ink</b>	UV				
<b>Colors</b>	CMYK	CMYK + WW	CMYK LcLm	CMYK LcLm + WW	CMYK x 2
<b>Capacity</b>	1 liter per color				
<b>Media</b>	<b>Max. printing width</b> 98" x 49" (2500mm x 1260mm) <b>Max. media width</b> 98" x 49" (2500mm x 1260mm) <b>Feeding System</b> Vacuum Table <b>Types</b> PS, PVC, MDF, Foam Board, Acrylics, Aluminum, Glass, etc.				
<b>Print Speed</b>	Draft 6 Passes	226 sq.ft./h ( 21 m <sup>2</sup> /h )		430 sq.ft./h ( 40 m <sup>2</sup> /h )	
	Standard 8 Passes	172 sq.ft./h ( 16 m <sup>2</sup> /h )		344 sq.ft./h ( 32 m <sup>2</sup> /h )	
	Quality 12 Passes	107 sq.ft./h ( 10 m <sup>2</sup> /h )		215 sq.ft./h ( 20 m <sup>2</sup> /h )	
	High Quality 16 Passes	86 sq.ft./h ( 8 m <sup>2</sup> /h )		172 sq.ft./h ( 16 m <sup>2</sup> /h )	
<b>Cleaning System</b>	Positive Pressure System and individual color purge controls				
<b>Interface</b>	USB 3.0				
<b>Maximum Carriage Height</b>	3.93" (100 mm)				
<b>Rip Software</b>	PhotoPrint OEM or MainTop RIP. FlexiPrint 12 Optional				
<b>Voltage</b>	AC 220 V, 50 Hz / 60 Hz				
<b>Power Consumption</b>	Vacuum power: 4500W (20 A) Printer: 154W (7 A)				
<b>Operational Temperature</b>	Temperature 68° - 77° F (20° - 25° C) Humidity 40 - 60%				
<b>Printer Dimensions (Length x Width x Height)</b>	152" x 85" x 45" (3871 x 2165 x 1150 mm)				
<b>Package Dimensions (Length x Width x Height)</b>	163" x 80" x 61" (4150 x 2050 x 1550 mm)				
<b>Printer Weight</b>	1157 lbs (525 kg)				
<b>Package Weight</b>	2105 lbs (955 kg)				